(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 17 February 2005 (17.02.2005)

(10) International Publication Number WO 2005/014945 A1

(51) International Patent Classification7: E04C 1/41, 2/284, 2/32, 2/34

E04B 1/76,

(21) International Application Number:

PCT/AU2004/001074

(22) International Filing Date: 11 August 2004 (11.08.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003904281 12 August 2003 (12.08.2003) ΑU 9 September 2003 (09.09.2003) AU 2003904928 2004900793 17 February 2004 (17.02.2004)

(71) Applicant and

- (72) Inventor: MINITER, Frederick, Michael [AU/AU]; 10/705 Pacific Highway, Gordon, NSW 2072 (AU).
- (74) Agent: FRASER OLD & SOHN; Level 6, 118 Alfred Street, Milsons Point, NSW 2061 (AU).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A THERMALLY INSULATING PANEL & WALL CONSTRUCTED THEREFROM



mould (201) which includes a former (227) preferably formed from egg carton cardboard, or similar. The former (227) is retained in situ. Film or foil (28, 228) in one or several layers is positioned in a cavity (12) formed between opposed panels to thereby create a plurality of thermal barriers in stagnant air. High thermal ratings for wall constructions are thereby able to be achieved.